

Coffee Grinders' Comparative Chart

ON DEMAND GRINDERS	Burrs	rpm		Average Output g/s		Hopper Capacity	Power	Grinding Adjustment Type			SweepOut system			
		mm	50hz	60hz	50hz			60hz	kg	W		Classic	Quick Set	Quick Set Gear Tech
												Micrometrical Stepless	Infinitesimal Stepless	Infinitesimal Stepless
E6P Brewing	Flat 64 brewing	1380	1650	2,5	3	0.6	300	●	×	×	×			
E5P	Flat 64	1380	1650	1,7	2	0.6	300	●	×	×	×			
E6P	Flat 64	1380	1650	1,7	2	0.6	300	●	×	×	×			
E7P	Flat 64	1480	1700	3	3,6	1.6	400	●	×	×	×			
E37J	Flat 64	1380	1650	1,7	2	0.6	300	×	●	×	×			
E37R	Flat 64	1480	1700	3	3,6	1.6	400	×	●	×	×			
E37S	Flat 83	1480	1700	4	5	1.6	500	×	×	●	×			
E37SL	Flat 83	1480	1700	4	5	1.6	500	×	×	●	×			
E37T	Flat 83 TiN plated	1480	1700	5	6	1.6	740	×	×	●	×			
E37K	Conical 71	360	290	5,5	4,5	1.6	850	×	×	●	×			
E37Z-Barista RS	Flat 83 Red Speed	1480	1700	4	5	1.2	900	×	×	●	●			

SINGLE DOSE GRINDERS	Burrs	rpm		Power	Grinding Adjustment Type			Steady Lock Grinder		
		mm	50hz		60hz	W	Classic		Quick Set	Quick Set Gear Tech
							Micrometrical Stepless		Infinitesimal Stepless	Infinitesimal Stepless
E37Z-Hero	Flat 83 DLC coated	600	1500	740	×	×	●	●		
E37Z-Naked	Flat 83 DLC coated	960	1150	740	×	×	●	●		
E37SD	Flat 83 Opalglide™ SD	960	1150	400	×	×	●	●		
E5SD	Flat 64 Opalglide™ SD	1380	1650	300	●	×	×	●		

	Sound Proofing	Thermal cut-out	Fan	Dose Setting	Dosing		Portafilter holder	Touch Display	Start	Shot Counter
					Free	Preset				
E37Z-Hero	×	●	●	×	●	×	×	×	toggle switch	×
E37Z-Naked	×	●	●	×	●	×	×	×	pulse button	×
E37SD	●	●	×	×	●	×	×	×	pulse button	×
E5SD	×	●	×	×	●	×	wtd cup holder	×	pulse button	×

	Steady Lock Grinder	Sound Proofing	Thermal cut-out	Fan	Dose Setting	Dosing		Porta-filter holder	Touch Display	Start	Shot Counter
						Free	Preset				
E6P Brewing	●	×	●	×	digital	●	●	wtd cup holder	●	pulse button	●
E5P	●	×	●	×	×	●	×	●	×	pulse button	×
E6P	●	×	●	×	digital	●	●	●	●	pulse button	●
E7P	●	×	●	×	digital	●	●	●	●	pulse button	●
E37J	●	●	●	×	digital	●	●	●	●	portafilter	●
E37R	●	●	●	×	digital	●	●	●	●	portafilter	●
E37S	●	●	●	×	digital	●	●	●	●	portafilter	●
E37SL	●	●	●	●	digital	●	●	●	●	portafilter	●
E37T	●	●	●	●	digital	●	●	●	●	portafilter	●
E37K	●	●	●	●	digital	●	●	●	●	portafilter	●
E37Z-Barista RS	●	×	●	●	digital	●	●	●	●	portafilter	●

RETAIL GRINDERS	Burrs	rpm		Average Output g/min		Hopper Capacity	Power	Grinding Adjustment Type					
		mm	50hz	60hz	50hz			60hz	kg	W	Classic	Quick Set	Quick Set Gear Tech
											Micrometrical Stepless	Infinitesimal Stepless	Infinitesimal Stepless
E8D	Flat 83 k110	1480	1700	270	330	1.6	740	×	●	×			

	Steady Lock Grinder	Sound Proofing	Thermal cut-out	Fan
E8D	●	●	●	●



Description: ● included X not available

Average output is calculated at standard Italian Espresso Consistency

(Italian Espresso basic numbers: 7g of ground coffee, 25-30 ml of espresso in 25-30s extraction time).

© Ceado srl - all rights reserved - 12/2022.

Data are indicative, referred to our internal tests. Designs and specifications of the products in this leaflet can be modified without prior notice. I dati riportati sono indicativi, riferiti a test interni. L'azienda si riserva di modificare in qualunque momento e senza preavviso le caratteristiche dei prodotti.

Ceado srl Spinea - Venezia, Italy - T +39 041 5030767 - www.coffee.ceado.com

